

Moon 3U
MN03 Underwater

- IP68
- IK04
- Class III
- CE certification
- Net Weight 0.8kgs
- Rubber cable 2M 2*0.824 mm2
- CREE COB LED
- SDCM<5
- Ra ≥ 80
- 3 or 5 Years Warranty



Use only in permanent immersion in water as to avoid damaging to LED!

General Data

Power	Lumen	CCT	Beam angle	Input voltage	Cover	Housing
3 Watt	240 lm	2700K 3000K 4000K 6000K	10°, 15°, 24°, 36°, 60°	AC12V as standard (AC100-245V 50/60Hz optional)	Stainless steel 316L	Stainless steel 316L

Dimension



Moon 8U
MN08 Underwater

- IP68
- IK04
- Class III
- CE certification
- Net Weight 1.6kgs
- Rubber cable 2M 2*0.824 mm2
- CREE COB LED
- SDCM<5
- Ra ≥ 80
- 3 or 5 Years Warranty



Use only in permanent immersion in water as to avoid damaging to LED!

General Data

Power	Lumen	CCT	Beam angle	Input voltage	Cover	Housing
8 Watt	700 lm	2700K 3000K 4000K 6000K	12°, 24°, 38°, 45°, 60°	AC12V as standard (AC100-245V 50/60Hz optional)	Stainless steel 316L	Stainless steel 316L

Dimension



